



302HQ GRADE

**TRUSS HEAD DOME HEAD  
STAINLESS STEEL**

**STAINLESS STEEL / STEEL**

Part No	Body	Mandrel	Body Dia. mm	Grip Range mm	Recommended mm	Body Length mm	Clearance mm	Head Dia. mm	Shear (N)	Tensile (N)	Inner Qty	Outer Qty
73STS41	Stainless Steel	Steel	3.2 (1/8)	Up to 1.6	3.3	5.15	7.4	6.65	1870	2360	1000	10000
73STS42	Stainless Steel	Steel	3.2 (1/8)	1.6-3.2	3.3	6.85	9.1	6.65	1870	2360	1000	10000
73STS43	Stainless Steel	Steel	3.2 (1/8)	3.2-4.8	3.3	8.35	10.6	8.45	1870	2360	1000	10000
73STS44	Stainless Steel	Steel	3.2 (1/8)	4.8-6.4	3.3	9.95	12.2	8.45	1870	2360	1000	10000
73STS46	Stainless Steel	Steel	3.2 (1/8)	7.9-9.5	3.3	13.45	15.7	8.45	1870	2360	1000	10000
73STS52	Stainless Steel	Steel	4.0 (5/32)	1.6-3.2	4.1	7.45	10.2	8.45	2890	3650	1000	10000
73STS53	Stainless Steel	Steel	4.0 (5/32)	3.2-4.8	4.1	9.05	11.8	8.45	2890	3650	1000	10000
73STS54	Stainless Steel	Steel	4.0 (5/32)	4.8-6.4	4.1	10.55	13.3	8.45	2890	3650	1000	10000
73STS55	Stainless Steel	Steel	4.0 (5/32)	6.4-7.9	4.1	12.05	14.8	8.45	2890	3650	1000	10000
73STS56	Stainless Steel	Steel	4.0 (5/32)	7.9-9.5	4.1	13.75	16.5	8.45	2890	3650	500	5000
73STS62	Stainless Steel	Steel	4.8 (3/16)	1.6-3.2	4.9	8.05	11.05	10	4230	5340	500	5000
73STS63	Stainless Steel	Steel	4.8 (3/16)	3.2-4.8	4.9	9.65	12.65	10	4230	5340	500	5000
73STS64	Stainless Steel	Steel	4.8 (3/16)	4.8-6.4	4.9	11.25	14.25	10	4230	5340	500	5000
73STS65	Stainless Steel	Steel	4.8 (3/16)	6.4-7.9	4.9	12.85	15.85	10	4230	5340	500	5000
73STS66	Stainless Steel	Steel	4.8 (3/16)	7.9-9.5	4.9	14.45	17.45	10	4230	5340	500	5000
73STS68	Stainless Steel	Steel	4.8 (3/16)	9.5-12.7	4.9	17.55	20.55	10	4230	5340	500	5000

The **Stainless Steel / Steel Truss Head** range is made from heading quality 302HQ grade stainless steel wire with a medium carbon content, zinc plated, steel mandrel to suit those applications where high tensile strengths and joint corrosion resistance are required. Manufactured by Spurway Cooke in Singapore, using only the highest quality wire available, you can be assured of the highest consistency and quality.

