



5056 GRADE

**COUNTERSUNK HEAD FLAT HEAD**

**ALUMINIUM / STEEL**

Part No	Body	Mandrel	Body Dia. mm	Grip Range mm	Recommended mm	Body Length mm	Clearance mm	Head Dia. mm	Shear (N)	Tensile (N)	Inner Qty	Outer Qty
72AS42	Aluminium	Steel	3.2 (1/8)	1.6-3.2	3.3	6.85	9.1	5.9	760	980	1000	10000
72AS43	Aluminium	Steel	3.2 (1/8)	3.2-4.8	3.3	8.35	10.6	5.9	760	980	1000	10000
72AS44	Aluminium	Steel	3.2 (1/8)	4.8-6.4	3.3	9.95	12.2	5.9	760	980	1000	10000
72AS45	Aluminium	Steel	3.2 (1/8)	6.4-7.9	3.3	11.55	13.8	5.9	760	980	1000	10000
72AS46	Aluminium	Steel	3.2 (1/8)	7.9-9.5	3.3	13.45	15.7	5.9	760	980	1000	10000
72AS52	Aluminium	Steel	4.0 (5/32)	1.6-3.2	4.1	7.45	10.2	7.4	1160	1560	1000	10000
72AS53	Aluminium	Steel	4.0 (5/32)	3.2-4.8	4.1	9.05	11.8	7.4	1160	1560	1000	10000
72AS54	Aluminium	Steel	4.0 (5/32)	4.8-6.4	4.1	10.55	13.3	7.4	1160	1560	1000	10000
72AS55	Aluminium	Steel	4.0 (5/32)	6.4-7.9	4.1	12.05	14.8	7.4	1160	1560	1000	10000
72AS56	Aluminium	Steel	4.0 (5/32)	7.9-9.5	4.1	13.75	16.5	7.4	1160	1560	500	5000
72AS62	Aluminium	Steel	4.8 (3/16)	1.6-3.2	4.9	8.05	11.05	8.9	1690	2220	500	5000
72AS63	Aluminium	Steel	4.8 (3/16)	3.2-4.8	4.9	9.65	12.65	8.9	1690	2220	500	5000
72AS64	Aluminium	Steel	4.8 (3/16)	4.8-6.4	4.9	11.25	14.25	8.9	1690	2220	500	5000
72AS66	Aluminium	Steel	4.8 (3/16)	7.9-9.5	4.9	14.45	17.45	8.9	1690	2220	500	5000
72AS68	Aluminium	Steel	4.8 (3/16)	9.5-12.7	4.9	17.55	20.55	8.9	1690	2220	500	5000
72AS610	Aluminium	Steel	4.8 (3/16)	12.7-15.9	4.9	21.45	24.45	8.9	1690	2220	500	5000

The Aluminium / Steel **Countersunk Head** range is made from 5056 grade aluminium alloy wire with a low carbon content, zinc plated, steel mandrel, to suit those applications where a higher tensile product, leaving a flush finish, is required. Manufactured by Spurway Cooke in Singapore, using only the highest quality wire available, you can be assured of the highest consistency and quality.

