



BLIND RIVET SOLUTIONS

GOLD COAST: Unit 1/13 John Duncan Crt
Varsity Lakes QLD 4227

Tel: 07 5593 4550 Fax: 07 5593 4549

email: coastsales@aerofast.com.au

ABN: 23 068 361 455 www.aerofast.com.au



5056 GRADE
TRUSS HEAD DOME HEAD

ALUMINIUM / STEEL

Part No	Body	Mandrel	Body Dia. mm	Grip Range mm	Recommended mm	Body Length mm	Clearance mm	Head Dia. mm	Shear (N)	Tensile (N)	Inner Qty	Outer Qty
73AS32*	Aluminium	Steel	2.4 (3/32)	1.6-3.2	2.5	6.15	8.15	5	310	360	1000	10000
73AS33*	Aluminium	Steel	2.4 (3/32)	3.2-4.8	2.5	7.75	9.75	5	310	360	1000	10000
73AS41	Aluminium	Steel	3.2 (1/8)	Up to 1.6	3.3	5.15	7.4	6.65	760	980	1000	10000
73AS42	Aluminium	Steel	3.2 (1/8)	1.6-3.2	3.3	6.85	9.1	6.65	760	980	1000	10000
73AS43	Aluminium	Steel	3.2 (1/8)	3.2-4.8	3.3	8.35	10.6	6.65	760	980	1000	10000
73AS44	Aluminium	Steel	3.2 (1/8)	4.8-6.4	3.3	9.95	12.2	6.65	760	980	1000	10000
73AS45	Aluminium	Steel	3.2 (1/8)	6.4-7.9	3.3	11.55	13.8	6.65	760	980	1000	10000
73AS46	Aluminium	Steel	3.2 (1/8)	7.9-9.5	3.3	13.45	15.7	6.65	760	980	1000	10000
73AS48	Aluminium	Steel	3.2 (1/8)	9.5-12.7	3.3	16.85	19.1	6.65	760	980	1000	10000
73AS410	Aluminium	Steel	3.2 (1/8)	12.7-15.9	3.3	20.25	22.5	6.65	760	980	1000	10000
73AS412	Aluminium	Steel	3.2 (1/8)	15.9-19	3.3	23.3	25.55	6.65	760	980	500	5000
73AS52	Aluminium	Steel	4.0 (5/32)	1.6-3.2	4.1	7.45	10.2	8.45	1160	1560	1000	10000
73AS53	Aluminium	Steel	4.0 (5/32)	3.2-4.8	4.1	9.05	11.8	8.45	1160	1560	1000	10000
73AS54	Aluminium	Steel	4.0 (5/32)	4.8-6.4	4.1	10.55	13.3	8.45	1160	1560	1000	10000
73AS55	Aluminium	Steel	4.0 (5/32)	6.4-7.9	4.1	12.05	14.8	8.45	1160	1560	1000	10000
73AS56	Aluminium	Steel	4.0 (5/32)	7.9-9.5	4.1	13.75	16.5	8.45	1160	1560	500	5000
73AS58	Aluminium	Steel	4.0 (5/32)	9.5-12.7	4.1	17.45	20.2	8.45	1160	1560	500	5000
73AS62	Aluminium	Steel	4.8 (3/16)	1.6-3.2	4.9	8.05	11.05	10	1690	2220	500	5000
73AS63	Aluminium	Steel	4.8 (3/16)	3.2-4.8	4.9	9.65	12.65	10	1690	2220	500	5000
73AS64	Aluminium	Steel	4.8 (3/16)	4.8-6.4	4.9	11.25	14.25	10	1690	2220	500	5000
73AS65	Aluminium	Steel	4.8 (3/16)	6.4-7.9	4.9	12.85	15.85	10	1690	2220	500	5000
73AS66	Aluminium	Steel	4.8 (3/16)	7.9-9.5	4.9	14.45	17.45	10	1690	2220	500	5000
73AS68	Aluminium	Steel	4.8 (3/16)	9.5-12.7	4.9	17.55	20.55	10	1690	2220	500	5000
73AS610	Aluminium	Steel	4.8 (3/16)	12.7-15.9	4.9	21.45	24.45	10	1690	2220	500	5000
73AS612	Aluminium	Steel	4.8 (3/16)	15.9-19	4.9	24.65	27.65	10	1690	2220	250	2500
73AS614	Aluminium	Steel	4.8 (3/16)	19-22.2	4.9	27.95	30.95	10	1690	2220	250	2500
73AS616	Aluminium	Steel	4.8 (3/16)	22.2-25.4	4.9	31.25	34.25	10	1690	2220	250	2500
73AS620	Aluminium	Steel	4.8 (3/16)	25.4-34.9	4.9	36	39	10	1690	2220	250	2500
73AS82	Aluminium	Steel	6.4 (1/4)	1.6-3.2	6.5	8.75	12.5	13.05	3110	4090	250	2500
73AS84	Aluminium	Steel	6.4 (1/4)	4.8-6.4	6.5	12.6	16.35	13.05	3110	4090	250	2500
73AS86	Aluminium	Steel	6.4 (1/4)	7.9-9.5	6.5	15.8	19.55	13.05	3110	4090	250	2500
73AS88	Aluminium	Steel	6.4 (1/4)	9.5-12.7	6.5	19	22.75	13.05	3110	4090	250	2500
73AS810	Aluminium	Steel	6.4 (1/4)	12.7-15.9	6.5	22.1	25.85	13.05	3110	4090	250	2500
73AS812	Aluminium	Steel	6.4 (1/4)	15.9-19	6.5	25.3	29.05	13.05	3110	4090	250	2500
73AS814	Aluminium	Steel	6.4 (1/4)	19-22.2	6.5	28.4	32.15	13.05	3110	4090	250	2500
73AS816	Aluminium	Steel	6.4 (1/4)	22.2-25.4	6.5	31.65	35.4	13.05	3110	4090	250	2500

* 73AS32 & 73AS33 are made from 5052 grade aluminium alloy wire with low carbon content, zinc plated, steel mandrel

The Aluminium / Steel Truss Head range is made from 5056 grade aluminium alloy wire with a low carbon content, zinc plated, steel mandrel, to suit those applications where a higher tensile product is required. Manufactured by Spurway Cooke in Singapore, using only the highest quality wire available, you can be assured of the highest consistency and quality.

